

Smart Pool Cleaner Foam roller change

Rest the unit on its right side and remove the black rubber cap. (Picture 1)



Picture 1

Remove the 3 screws. (Picture 2)



Picture 2

Pull of the grey end cap. (Picture 3)



Picture 3

Lift of the roller. (Pictures 4 & 5)



Picture 4

picture5

Slide the foam pad down to expose the 2 screws in the black inner roller (Pictures 6 & 7). The ends of the foam may need to be soaked for a while to make it easier to slide down (Picture 8).



Picture 6

picture 7

picture8

Once both screws have been removed the roller tube can be split in half (Picture 9).



Picture 9

Remove the foam pad from the remaining half of the roller tube (Picture 10).



Picture 10

Fit the first rubber brush pad to the roller ensuring that the holes in the brush pad line up with the lugs on the roller tube (Picture 11).



Picture 11

Pull the ends of the rubber brush pad together and pull the ties through the holes to fasten the ends together (Picture 12).



Picture 12

Fit the foam insert onto the roller tube and join the 2 halves of the roller tube back together with the 2 screws removed earlier (Picture 13).



Picture 13

Fit the second rubber brush pad to the roller tube (Picture 14).



Picture 14

Refit the completed roller tube onto the body of the cleaner (Picture 15).



Picture 15

**Refit the grey end cap with the 3 screws removed earlier
(Picture 16).**



Picture 16

Refit the black rubber cap (Picture 17).



Picture 17

Your unit is now ready to use.